



Using rotation laser RL 04




Aligning partition walls



Transferring heights



Hanging ceilings



Setting right angles



Leveling work on ceiling and floor panels



Use with ground hoop



Use with tilting wedge

Designation	Art. No.	
Aluminum elevator tripod	0714 649 13	1
Wall bracket	0714 64 437	
Charging cable	0714 640 225	
Ground hoop	0714 640 127	
Tilting wedge	0714 649 128	
Remote control	0714 640 221	
1/4" tripod plate	0714 649 126	

Hand-Held Receiver for Rotation Laser

High-performance laser receiver for indoor and outdoor use

LE 100

- Polycarbonate plastic housing.
→ Extremely jolt-resistant.
- Protection class IP 67 – dust-proof and watertight.
→ Suitable for use under extremely dusty conditions and in continuous rain.
- LED display on front and back.
→ Can be read easily and accurately.
- Integrated retaining magnet.
→ Can be fastened to magnetic surfaces.
- With acoustic signal.



Art. No. 0714 640 140

Plastic holder included in delivery scope.

Technical data

Working range	approx. 100 m
Display	3 LEDs
Reception field	120°
Batteries	2 x AA/Mignon
Clamping range	50 mm

LE 150

- Polycarbonate plastic housing.
→ Extremely jolt-resistant.
- Protection class IP 67 – dust-proof and watertight.
→ Suitable for use under extremely dusty conditions and in continuous rain.
- LCD display on front and back.
→ Can be read easily and convenient.
- With adjustable acoustic signal.
→ Tone signal can be adapted to ambient noise level.
- Two accuracy levels.
→ Sensitivity of receiver can be adapted to application.



Art. No. 0714 640 141

Plastic holder included in delivery scope.

Technical data

Working range	approx. 150 m
Display	LED / LCD
Reception field	approx. 120°
Batteries	2 x AA/Mignon
Clamping range	50 mm