

Sehr hohe Abtragsleistung bei gutem Finish

Sehr hohe Standzeit

Angenehmes, staubfreies Schleifen dank neuer 7-Loch und 9-Loch Staubabsaugungstechnologie
Hohe Flexibilität auch im Grobkorn, deshalb hervorragend für manuellen Einsatz

Speziell für den Kfz-Bereich entwickelt

Eignet sich hervorragend auf harten Füllern, Spachtel, Werksgrundierungen und Composite Werkstoffen dank speziellem Korn

- Schleifen von Spachtel / Polyester / GFK
- Ausschleifen von Übergängen und Nachschleifen von Spachtel und Polyester
- Ausschleifen von Übergängen, Planschliff v. Spachtel
- Nachschleifen / Feinschleifen von Spachtel
- Schleifen von Werksgrundierungen
- Schleifen von Werksgrundierungen
- Planschleifen / Feinschleifen v. Füller
- Formschleifen von Füller
- Mattieren von Lackierungen
- Feinschliff / Endschliff

Korn 40-80
Korn 80-320
Korn 80-120
Korn 150-320
Korn 240-320
Korn 240-400
Korn 320-500
Korn 320-600
Korn 500-600
Korn 800 - 2500

Korntyp: Aluminiumoxyd

Unterlage: Korn 40 - 100 C-Papier (120g/m²)
Korn 120 - 600 B-Papier (100g / m²)
Korn 800 - 2500 PE-Folie

Bindung: Kunstharz

Streuart: Korn 40 - 600 elektrostatisch halboffen
Korn 800 - 2500 offene Streuung

Farbe: Korn 40 - 600 gelb
Korn 800 - 2500 blau

Very high stock removal and good finish

Very good lifetime

Dust free sanding thanks to new 7-hole dust extraction technology.

High flexibility of abrasive, also in coarser grits, ideal for manual use

Especially developed for automotive applications

Very good performance on hard fillers, primers and composite materials, thanks to special grain type.

- Sanding of filler, polyester and composites
- Keying of feather edges and final sanding of bodyfiller / polyester
- Keying of feather edges, sanding of filler
- Final sanding of filler
- Sanding of new components / work primers
- Sanding of new components / work primers
- Final sanding of filler
- Shaping of primer filler
- Scuffing lacquers
- fine grinding / end grinding

grid 40-80
grid 80-320
grid 80-120
grid 150-320
grid 240-320
grid 240-400
grid 320-500
grid 320-600
grid 500-600
grid 800 - 2500

Grain type: Aluminiumoxyd

Underlay grid 40 - 100 C-paper (120g/m²)
grid 120 - 600 B-paper (100g / m²)
grid 800 - 2500 PE-film

Bindung: synthetic resin

Coating state: grid 40 - 600 electrostatic half open
grid 800 - 2500 open coating

colour: grid 40 - 600 yellow
grid 800 - 2500 blue

				Farbe: gelb Colour: yellow																Farbe: blau Colour: blue					
				Körnung/ velcro grain	40	60	80	100	120	150	180	220	240	320	400	500	600	800	1000	1200	1500	2000	2500		
		Kleff/ ohne/ plain	Artikelnummern article number																						
Ø 75mm		X	5506 341 0..																						
Ø 150 mm		X	5506 343 0..																						
Ø 150 mm 7 Loch / hole		X	5506 313 0..																						
Ø 150 mm 9 Loch / hole Festo		X	5506 303 0..																						
280 x 115 mm		X	5506 143 1..																						
230 x 280 mm		X	5506 144 1..																						
115 x 230mm 10-Loch		X	5506 132 0..																						
70x125mm 8-Loch		X	5506 128 0..																						
70x198mm 8-Loch		X	5506 129 0..																						
81 x 153mm 8-Loch		X	5506 126 0..																						
70 x 420mm 14-Loch		X	5506 157 0..																						
Rolle 50m x 115mm		X	5506 247 1..																						
Rolle 50m x 75mm		X	5506 240 0..																						
Rolle 50m x 95mm		X	5506 241 0..																						
Rolle 25m x 115 mm	SOFT ROLL	X	5506 442 1..																						